



TOOTH FACES AND TOP SHARPENING MACHINE FOR CARBIDE TIPPED CIRCULAR SAWS



NM 100

nimoch.com

SPECIFICATIONS

Circular saw diameter	Φ120 ~ Φ800mm
Bore	Φ16 ~ Φ120mm
Max blade thickness	6mm
Tooth pitch	7 ~ 60mm
Rake angle	-10° ~ +40°
Clearance angle	6 ~ 45°
Bevel grinding top & face	Top 45°/ Face 45°
Range of grinding cycle	Max 25mm (adjustable)
Grinding speed	0.5 ~ 6mm/s
Feed speed	Max 13 tooth/min
Grinding wheel outside diameter	Φ125mm
Grinding wheel linear speed	28m/s
Hydraulic dial tooth (Direct dial)	
Spindle servo feed	
Coolant pump flow	25L/min
Coolant pump capacity	80L
Total power	2.8KW

CHINA

Nimo Guangzhou Technology Co. Ltd.
No. 5 Huasui Road Zhujiang New Town
Guangzhou, 1168
evandro@nimocn.com
WhatsApp: +86 189 0229 6147

USA

Nimo America LLC.
990 S Rogers Circle, Suite 11
Boca Raton, FL 33487
sales@nimocn.com
WhatsApp: +1 954 240 2002

BRAZIL

Nimo Brasil Importação e Exportação Ltda.
Av Ordem e Progresso, 157 - Conj 1108
São Paulo - SP, 01141-030
nicolas@nimocn.com
WhatsApp: +55 11 9 9138 9138

www.nimocn.com

